



SUPERIOR HOLDING POWER,
LIGHTWEIGHT, DURABLE & REUSABLE.
INCREASE YOUR PRODUCTIVITY

Baytex Earth Anchors

Increase your productivity with the screw in, screw out reusable earth anchors. Lightweight aircraft-quality cast aluminium 356 alloy.

SIMPLICITY · PERFORMANCE · STYLE



Earth Anchor Load Capacity Pull Out Resistance

SOIL CLASS	PE9 PE9T 23cm (9")		PE10 25cm (10")	PE14-STD 37cm (14")	PE18 PE18-33 PE18SQ 46cm (18")	PE26 PE26-33 66cm (26")	PE36 91cm (36")	PE46 Hex PE46 Guy 1.2m (46")
	hardpan/ashphalt/clay							
1 Cohesive soil	1.78 kN (181 kg)		4.45 kN (454 kg)		11.1 kN (1311 kg)	20.0 kN (2039 kg)	37.4 kN (3814 kg)	62.3 kN (6351 kg)
2 Medium density soil	0.89 kN (91 kg)		3.11 kN (317 kg)		7.56 kN (771 kg)	13.8 kN (1407 kg)	26.9 kN (2743 kg)	42.3 kN (4312 kg)
3 Loose med-to-fine sand	0.44 kN (45 kg)		1.56 kN (159 kg)		2.67 kN (272 kg)	4.89 kN (498 kg)	9.34 kN (952 kg)	14.7 kN (1498 kg)
4 Loose fine uncompacted sand	0.44 kN less than (45 kg)		0.89 kN (91 kg)		1.56 kN (159 kg)	2.80 kN (285 kg)	4.45 kN (453 kg)	8.90 kN (907 kg)
	0.44 kN less than (45 kg)		0.44 kN (45 kg)		0.89 kN (91 kg)	1.60 kN (163 kg)	1.56 kN (159 kg)	4.89 kN (498 kg)

PE9 20mm hex head 32mm flange 16mm neck diameter 29mm flight diameter 23cm	PE9T 10cm handle 13mm neck diameter 29mm flight diameter	PE10 26mm hex head 5cm flange 26mm neck diameter 45mm flight diameter 25cm 0.5kg	PE14-STD 15cm steel stud with washer & nut 5cm flange 36mm neck diameter 58mm flight diameter 37cm 30cm 0.85kg Tapped hole: 1/2" 113 thread 64mm depth 1/2" square drive	PE18SQ 1/2" square drive 5cm flange 26mm neck diameter 45mm flight diameter 46cm .6kg
--	--	---	--	--

PE18 26mm hex head 5cm flange 26mm neck diameter 45mm flight diameter 46cm 0.7kg Base Plate: 7mm plate = 39mm hole / 13mm plate = 42mm hole	PE26 26mm hex head 5cm flange 26mm neck diameter 45mm flight diameter 66cm 0.7kg	PE36 Hex 51mm hex head 10cm flange 45mm neck diameter 77mm flight diameter 90cm 4.0kg Tapped for 3/8" bolt 9.5mm clear hole for sleeve bolt or grounding wire	PE46 Hex 51mm hex head 10cm flange 45mm neck diameter 77mm flight diameter 1.2m 4.8kg	PE46 Guy 51mm hex head 45mm neck diameter 77mm flight diameter 4.6kg 51mm hex head slot for cable up to 13mm
PE18-33 26mm hex head 5cm flange 26mm neck diameter 33mm flight diameter 46cm 0.7kg Base Plate: 7mm plate = 30mm hole	PE26-33 26mm hex head 5cm flange 26mm neck diameter 33mm flight diameter 66cm 0.7kg			

New Zealand

52 Newton Street,
PO Box 4370, Mount Maunganui
New Zealand

tel +64 7 579 0190
fax +64 7 579 0194
www.baytex.co.nz

Australia

tel 02 4340 4144
mob 0400 312 314



PE9-PE26

Milwaukee Cordless Impact Wrench M18
1/2" Drive 950 NM Torque
(M18CHIWF12-502C)



1" 6-Sided Long-reach
Impact Socket 1/2" Drive



Ships Auger 11/16"x400mm



7/16" to 1/2" Hex to
Ships Auger Coupling

PE36-PE46

Matika Electric Impact Wrench
1" Drive (MAK-TW1000)



2" 6 pointed LR
Impact Socket 1" Drive



Earth Auger Adaptor Coupling 1"
square drive to fit 2"



Earth Auger 2"x 36"



RECOMMENDED TOOLS

Baytex Earth Anchors

SIMPLICITY · PERFORMANCE · STYLE

