

## PRODUCT SPECIFICATIONS

DX12 is a medium weight, general-pupose blended poly/cotton canvas which is especially suitable for a wide range of applications. These include: swags, marquee and tepee roofs and walls, temporary shelters, under tarpaulins, box-trailer covers and heavy-duty campervan roofs and walls. DX12 is also perfect for annexe roofs in semi-permanent situations, as well as high quality family marquee roofs and walls.

Weight:	Dynaproofed: 505g/sq.m (14.9 oz) +/- 30gsm			
Width:	Dynaproofed: 204cm			
Construction:	Woven 52/48 Poly/Cotton Plain Weave. 22.8 ends per cm. 15 picks per cm. Yarn Count 2/12 ECC x 2/12 ECC.			
Maximum Shrinkage:	2.5% in Warp			
Tear Resistance: (AS 2001.2.10)	WARP – 116N WEFT – 68N			
Breaking Force: (AS 2001.2.3)	WARP – 2195N WEFT – 1523N			
Hydrostatic Head: (AS 2001.2.17)	800mm min			
Cone Test: (AS 2001.2.18)	Pass			
Colours available on request:				
Brunswick Green	Antelope	Blue		Maroon
Grey	Olive	Khaki		Green
Lt. Grey	Black	Navy	9	Aus Cam D.P
Beige	Lt. Sand	Dark Green		Olive F/R*
*Flammability: Olive F/R tested to AS1530 Part 3 Results available on request				

## Caring for your Canvas:



## **Recommendations for Use and Maintenance**

Waterproofed canvas has been used in Australia since the early days of settlement for protection from the harsh and unpredictable Australian climate. Canvas remains the traditional Australian fabric for weather protections and recreational covers due to its breathability, comparatively light weight, natural cotton appearance.

Dynaproofed Canvas is Australian for canvas. It is proudly produced in Australia to meet the most severe of weather conditions. The outback Rugged composition provides assurance for the most demanding applications such as Road Train haulage across Nullabor, Tent and Camper Trailers on 4WD adventures, and even the old faithful canvas swag for sleeping under the stars.

The Dynoproofed Canvas range is the trusted Aussie canvas and made in a range of specialised fabrics to perform in specific situations.

## Care instructions: -

- New canvas should be thoroughly wet before use and allowed to dry.
  Repeat 2-3 times to ensure sealing up of the seams.
- · Clean only with cold watcher and brush do not use soap or detergent.
- · Ensure product is completely dry prior to storage.
- · Do not expose to petrol, oil or solvents.
- Restore well worn products with DYNAPROOF.

Note: Dynaproofed Canvas is an Industrial Textile. From time to time, it may be subject to random aesthetic imperfections. These imperfections are cosmetic only and will not impact at all on the performance of this high quality canvas.







Wax Converters Textiles

Wax Converters textiles Pty Ltd. 21 James St, Lidcombe NSW 2141